

CLAIMS

1. (Currently Amended) A diffraction grating element, comprising:
 - a first medium having a refractive index of n_1 and a thickness of 5 μ m or more;
 - a second medium arranged so as to be in contact with said first medium, said second medium having a refractive index of n_2 lower than that of said first medium and a thickness of 5 μ m or more; [[and]]
 - a diffraction grating provided at the interface between said first medium and said second medium[[.]];
 - a first anti-reflection film provided on a surface of said first medium so as to sandwich said first medium together with said second medium; and
 - a second anti-reflection film provided on a surface of said second medium so as to sandwich said second medium together with said first medium,
- wherein one of said first medium and said second medium is a solid, and the other thereof is a solid or a liquid, and
- wherein, taking the period of said diffraction grating to be Λ , the height of said diffraction grating to be H , the duty ratio of the width of said first medium with respect to the period Λ in said diffraction grating to be f , and the normalized height expressed by $(n_1/n_2-1) H/\Lambda$ to be H_{norm} , in a two-dimensional plane based on coordinate values (H_{norm}, f) , the normalized height H_{norm} and the duty ratio f lie within a region enclosed by linking in sequence, by means of line segments, the point (0.50, 0.32), the point (0.50, 0.75), the point (2.00, 0.90), the point (4.00, 0.90), the point (2.20, 0.76), the point (0.75, 0.32), and the point (0.50, 0.32), or within a region enclosed by linking in sequence, by means of line segments, the point (2.25, 0.20), the point (2.25, 0.44), the point (2.75, 0.44), the point (2.75, 0.20), and the point (2.25, 0.20).

2. (Original) A diffraction grating element according to claim 1, wherein, in the two-dimensional plane based on coordinate values (H_{norm} , f), the normalized height H_{norm} and the duty ratio f lie within a region enclosed by linking in sequence, by means of line segments, the point (0.60, 0.50), the point (0.60, 0.75), the point (2.00, 0.88), the point (2.40, 0.88), the point (1.50, 0.70), the point (1.10, 0.50), and the point (0.60, 0.50).

3. (Original) A diffraction grating element according to claim 1, wherein, in the two-dimensional plane based on coordinate values (H_{norm} , f), the normalized height H_{norm} and the duty ratio f lie within a region enclosed by linking in sequence, by means of line segments, the point (0.80, 0.62), the point (0.80, 0.65), the point (1.00, 0.75), the point (1.60, 0.82), the point (1.75, 0.82), the point (0.96, 0.60), and the point (0.80, 0.62).

4. (Original) A diffraction grating element according to claim 1, wherein the period Λ of said diffraction grating element is 1.46 μm or less.

5. (Original) A diffraction grating element according to claim 1, wherein the refractive index ratio (n_1/n_2) between said first medium and said second medium is 1.25 or more but 1.6 or less.

6. (Original) An optical module including a diffraction grating element according to claim 1, said optical module multiplexing or demultiplexing light by using said diffraction grating element.

7. (Currently Amended) An optical module according to claim ~~[[6]]~~ 11, wherein the incident angle or the diffraction angle of the light in said second medium of said diffraction grating element is 60° or less.

8. (Currently Amended) An optical module according to claim ~~[[6]]~~ 11, wherein the incident angle or the diffraction angle of the light in said second medium of said diffraction grating element is 25° or more but 35° or less.

9. (Currently Amended) An optical communications system including an optical module according to claim ~~[[6]]~~ 11, said optical communications system transmitting signal light, and multiplexing or demultiplexing the signal light by using said optical module.

10. (Original) An optical communications system according to claim 9, wherein, in a signal wavelength band, a Bragg condition of said diffraction grating in said diffraction grating element included in said optical module is satisfied.

11. (New) An optical module according to claim 6, further comprising a third material having a refractive index of n_0 lower than those of said first and second mediums and covering an upper surface of said diffraction grating element; and a fourth material having a refractive index of n_0 lower than those of said first and second mediums and covering a lower surface of said diffraction grating element opposing said upper surface.